## **Product Information**



A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA

## **VALVOLINE SYNPOWER SAE 5W30 MOTOR OIL**

**Valvoline SynPower SAE 5W30 Motor Oil** is a premium fully synthetic motor oil, formulated with the highest quality synthetic base oils and enhanced with the most advanced additive technology for ultimate performance in meeting the requirements for virtually all high performance cars like Mercedes Benz, BMW & VW and light trucks (vans) including gasoline, diesel, and LPG engines.

**Valvoline SynPower SAE 5W30 Motor Oil** provides the highest level of protection under severe service conditions and meet the performance requirements of virtually all naturally aspirated, turbo charged and super charged passenger cars.

The Valvoline SynPower Motor Oil advantages

• Breakdown Resistance: Increases thermal and oxidation stability

Deposit Control: Reduces formation of sludge and varnish deposits
Wear Protection: Improves oil film strength and breakdown resistance

• Volatality: Lowers oil vaporization and consumption at extreme

conditions

Cold start Properties:
Oil flows easily at low temperatures

Performance levels / Approvals	Typical Characteristics	
API SM / SL / CF	Kinematic Viscosity, cSt @ 100°C	11.2
	Viscosity Index	164
	TBN, mg KOH/g (ASTM D-2896)	7.2
	Pour Point, °C, Max.	-36
	Flash Point, COC, °C	210
	CCS @ -30 oC, cP, Max.	6600

Available configurations: 6 x 1L case (686031), 4 x 4L case (685850)

This information only applies to products manufactured in the following location(s) – Singapore